

View Online at <https://aerobasegroup.com/nsn/5305-01-376-3573>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.874 inches

**Fastener Length:**

Between 0.969 inches and 1.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.557 inches and 0.577 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.082 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

7850 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.865 inches first hole and 0.885 inches first hole

**Material:**

Steel

**Material Specification:**

Sae j429, grade 8 assn standard all material responses

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, type z, class 2 military specification all treatment responses

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 8 grade and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-p-16232 spec.