## NSN 5305-01-376-4762

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-376-4762 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.460 inches and 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.190 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unf

## NSN 5305-01-376-4762

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
-------------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0