

NSN 5305-01-376-4763 Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-376-4763 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Knurled no. 5

Head Diameter: 0.375 inches

0.500 inches **First Diameter From Head:**

0.118 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Head Height:

0.875 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1 Material:

Steel comp 631

Material Specification:

Astm a564 assn standard single material response

Surface Treatment:

Cadmium and passivate

Surface Treatment Specification:

Qq-p-416 ty1 cl1 federal specification single treatment response and qq-p-35 federal specification single treatment response

NSN 5305-01-376-4763 Externally Relieved Body Screw - Page 2 of 2



| Thread Series Designato |
|-------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0