

View Online at <https://aerobasegroup.com/nsn/5305-01-376-4768>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.067 inches and 1.097 inches

Head Style:

Knurled no. 5

Head Diameter:

0.451 inches

Head Height:

0.360 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.094 inches and 0.155 inches

Thread Diameter:

0.190 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

32

Material:

Aluminum alloy 6061 headsteel comp 301 secondary washersteel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offstainless steel fastener

Material Specification:

Qq-a-225/8, t6 federal specification single material response headmil-s-5059 military specification single material response secondary washermil-s-5059 military specification single material response primary washerastm a580 assn standard single material response springqq-a-225/8, t6 federal specification single material response stand-offastm a493, 300 series assn standard all material responses fastener

Surface Treatment:

Anodize headpassivate secondary washerpassivate primary washerpassivate springanodize stand-offpassivate fastener

Surface Treatment Specification:

Mil-a-8625, type 1, class 1 military specification single treatment response headqq-p-35 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-s-8625, type 1, class 1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No