NSN 5305-01-376-5289

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-376-5289
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.760 inches and 0.790 inches
Head Style:
Knurled no. 5
Head Diameter:
0.340 inches
Head Height:
0.356 inches
Internal Drive Style:
Hexagon
Material Accommodated Thickness:
Between 0.020 inches and 0.031 inches
Thread Diameter:
0.138 inches
Width Across Flats:
0.109 inches
Thready Qty Per Inch (tpi):
32
Material:
Aluminum alloy 6061 headsteel comp 301 secondary washersteel comp 301 primary washersteel comp 302 springaluminum alloy 6061
stand-offstainless steel fastener
Material Specification:
Qq-a-225/8, t6 federal specification single material response headmil-s-5059 military specification single material response secondary
washermil-s-5059 military specification single material response primary washerastm a580, cond b assn standard single material response
springqq-a-225/8, t6 federal specification single material response stand-offastm a493, 300 series assn standard all material responses
fastener
Surface Treatment:
Anodize headpassivate secondary washerpassivate primary washerpassivate springanodize stand-offpassivate fastener
Surface Treatment Specification:
Mil-a-8625, type 1, class 1 military specification single treatment response headqq-p-35 federal specification single treatment response
secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment
response springmil-s-8625, type 1, class 1 military specification single treatment response stand-offqq-p-35 federal specification single
treatment response fastener
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

N

Demilitarization: