

View Online at <https://aerobasegroup.com/nsn/5305-01-376-5500>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.470 inches

Fastener Length:

Between 0.830 inches and 0.860 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.592 inches and 0.612 inches

Head Height:

Between 0.176 inches and 0.188 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6047 military specification 5th material response or ams6300 assn standard 6th material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.