## NSN 5305-01-376-5502

Machine Screw - Page 1 of 2

**Thread Class:** 

**Right-hand** 

**Thread Direction:** 

3a

View Online at https://aerobasegroup.com/nsn/5305-01-376-5502



## **Thread Length:** Between 1.359 inches and 1.468 inches Fastener Length: Between 1.421 inches and 1.468 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.243 inches and 0.251 inches Internal Drive Style: Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, cl2 ty2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

--

## Demilitarization:

No

## NSN 5305-01-376-5502

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

