## NSN 5305-01-377-6177

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-377-6177 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.661 inches **Fastener Length:** 0.710 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Screw Material Specification:** Qq-s-763 federal specification all material responses and fed-std66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A500d0