NSN 5305-01-377-6548

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-377-6548 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.942 inches **Fastener Length:** 6.2095 inches **Head Style:** Double chamfer **Head Diameter:** 0.265 inches **Head Height:** 0.2165 inches **First Diameter From Head:** 0.162 inches **Second Diameter From Head:** 0.1257 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 4.2275 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 5.2675 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.140 inches and 0.155 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** 0.920 in. Long wrenching flats on shank, cross section is 0.168 in. Across flats by 0.187 in. Material: Steel comp 631 **Material Specification:** Ams 5673 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 type 1, type 2 or type 3 federal specification single treatment response

NSN 5305-01-377-6548

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0