

View Online at <https://aerobasegroup.com/nsn/5305-01-377-6548>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.942 inches

**Fastener Length:**

6.2095 inches

**Head Style:**

Double chamfer

**Head Diameter:**

0.265 inches

**Head Height:**

0.2165 inches

**First Diameter From Head:**

0.162 inches

**Second Diameter From Head:**

0.1257 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

4.2275 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

5.2675 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.140 inches and 0.155 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

0.920 in. Long wrenching flats on shank, cross section is 0.168 in. Across flats by 0.187 in.

**Material:**

Steel comp 631

**Material Specification:**

Ams 5673 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 1, type 2 or type 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0