Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-377-9986

| Thread Class: |
|---|
| |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.390 inches |
| Fastener Length: |
| 0.470 inches |
| Head Style: |
| Hexagon extended washer |
| Head Height: |
| 0.160 inches |
| Width Between Flats: |
| 0.500 inches |
| Extended Washer Diameter: |
| 0.440 inches |
| Extended Washer Thickness: |
| Between 0.010 inches and 0.030 inches |
| First Diameter From Head: |
| Between 0.300 inches and 0.310 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.310 inches and 0.340 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| Material: |
| Nickel alloy |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |