NSN 5305-01-378-3966

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-378-3966

Thread Class.
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.527 inches and 0.620 inches
Fastener Length:
Between 0.589 inches and 0.620 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.231 inches and 0.279 inches
Locking Feature:
Patch
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Locking Feature Material:
Plastic polyamide
Locking Feature Material Specification:
Mil-f-18240 military specification single material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, cl2, ty2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-378-3966

Machine Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.