NSN 5305-01-378-7842

Thread Class:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-378-7842

Thread Direction:
Right-hand
Thread Length:
Between 0.917 inches and 1.000 inches
Fastener Length:
Between 0.969 inches and 1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.158 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Hardness Rating: 39.0 rockwell c and 45.0 rockwell c
-
39.0 rockwell c and 45.0 rockwell c
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel Material Specification:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel Material Specification: Fed 66 federal standard all material responses
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel Material Specification: Fed 66 federal standard all material responses Surface Treatment:
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel Material Specification: Fed 66 federal standard all material responses Surface Treatment: Cadmium and chromate
39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Surface Finish: 32.0 microinches threads Color: Bronze or olive drab Material: Steel Material Specification: Fed 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification:

NSN 5305-01-378-7842

Socket Head Cap Screw - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0