Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-378-8732

View Online at https://aerobasegroup.com/nsn/5305-01-378-8732
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.125 inches
Fastener Length:
4.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.308 inches and 0.312 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, cl2, ty2 federal specification single treatment response
Thread Series Designator:

Unrf

NSN 5305-01-378-8732

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0