## NSN 5305-01-378-9334



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-378-9334 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.944 inches and 1.000 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.244 inches and 0.250 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 10s style Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0