## NSN 5305-01-379-0560

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-379-0560 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response and ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1531 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-379-0560

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0