NSN 5305-01-379-4175

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-379-4175

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.375 inches and 1.500 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.107 inches and 1.125 inches
Head Height:
Between 0.740 inches and 0.750 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.625 inches and 0.631 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Surface Finish:
32.0 microinches threads
Color:
Bronze or olive drab
Material:
Steel
Material Specification:
Fed 66 federal standard all material responses
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Mil-std-171, 1.9.2.3 military standard single treatment response
Thread Series Designator:

Unc

NSN 5305-01-379-4175

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-std-171 spec.

Shelf Life: