

<b>NSN 5305-01-379-4350</b> Machine Screw - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5305-01-379-4350
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
Between 2.210 inches and 2.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Width Between Flats:
Between 0.1094 inches and 0.1111 inches
Internal Drive Style:
Err-090
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.1094 inches and 0.1111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 33.0 rockwell c and 42.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unrc

**Specification Data:** 

80205-nas1531 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-379-4350

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

