Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-379-9830



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.525 inches and 0.625 inches

#### Fastener Length:

0.625 inches

#### Head Style:

Flat chamfer

#### Head Diameter:

Between 0.365 inches and 0.375 inches

#### **Head Height:**

Between 0.244 inches and 0.250 inches

### **Internal Drive Style:**

Hexagon

#### Thread Diameter:

0.250 inches

#### Width Across Flats:

Between 0.187 inches and 0.190 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

33.0 rockwell c and 42.0 rockwell c

#### **Minimum Yield Strength:**

120000 pounds per square inch

# Color:

Black

### Material:

Iron alloy 660

### Material Specification:

Ams5731 assn standard single material response and ams5737 assn standard single material response

### Surface Treatment:

Oxide

## Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

# Thread Series Designator:

Unrc

## Shelf Life:

N/a

# NSN 5305-01-379-9830

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

