

View Online at <https://aerobasegroup.com/nsn/5305-01-380-3424>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.494 inches and 0.625 inches

**Fastener Length:**

Between 0.594 inches and 0.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.365 inches and 0.375 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Mrap - m-atv with cs13 pop and sne

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.188 inches and 0.190 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Color:**

Olive drab

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Qq-z-325, ty2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0