NSN 5305-01-380-3424

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-3424 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.494 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **End Application:** Mrap - m-atv with cs13 pop and sne **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Color: Olive drab Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Qq-z-325, ty2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-380-3424

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0