

View Online at <https://aerobasegroup.com/nsn/5305-01-380-3590>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.200 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.178 inches and 0.183 inches

**Head Height:**

Between 0.059 inches and 0.069 inches

**Hole Diameter:**

Between 0.034 inches and 0.042 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.112 inches

**Hole Quantity:**

2

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5737 assn standard single material response

**Screw Surface Treatment:**

Passivate and chromate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response and qq-p-416, type 2 federal specification 2nd treatment response

**Head Hole Configuration Style:**

Round

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1101 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0