## NSN 5305-01-380-3590

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-3590

Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.200 inches and 0.250 inches						
Fastener Length:						
Between 0.219 inches and 0.250 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.178 inches and 0.183 inches						
Head Height:						
Between 0.059 inches and 0.069 inches						
Hole Diameter:						
Between 0.034 inches and 0.042 inches						
Internal Drive Style:						
Torque set						
Thread Diameter:						
0.112 inches						
Hole Quantity:						
2						
Thready Qty Per Inch (tpi):						
40						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Screw Material:						
Iron alloy 660						
Screw Material Specification:						
Ams 5737 assn standard single material response						
Screw Surface Treatment:						
Passivate and chromate						
Screw Surface Treatment Specification:						
Qq-p-35 federal specification 1st treatment response and qq-p-416, type 2 federal specification 2nd treatment response						
Head Hole Configuration Style:						
Round						
Thread Series Designator:						
Unjc						
Specification Data:						
80205-nas1101 professional/industrial association standard						
Shelf Life:						
N/a						

## NSN 5305-01-380-3590

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A500d0