NSN 5305-01-380-4526

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-4526 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.110 inches **Fastener Length:** 0.180 inches **Head Style:** Flat extended washer **Head Diameter:** 0.160 inches **Head Height:** 0.160 inches **Extended Washer Diameter:** 0.245 inches **Extended Washer Thickness:** 0.080 inches **First Diameter From Head:** Between 0.148 inches and 0.150 inches **Second Diameter From Head:** 0.064 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.045 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.070 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 56 **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:**

Astm a582 assn standard single material response

Surface Treatment:

Passivate

NSN 5305-01-380-4526

Externally Relieved Body Screw - Page 2 of 2



Qq-p-35 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0