NSN 5305-01-380-7092

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-7092 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** 0.715 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.4640 inches and 0.5066 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Hexagon **End Application:** Agm129a **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Width Across Flats: Between 0.1562 inches and 0.1580 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Criticality Code Justification:** Anee and aaur Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response Mil-c-83488, cl3, ty2 military specification single treatment response

Surface Treatment Specification: Thread Series Designator: Unjf Shelf Life: N/a

NSN 5305-01-380-7092

Close Tolerance Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.