## NSN 5305-01-380-7092

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-7092

view Online at https://aerobasegroup.com/nsn/5305-01-380-7092
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
0.715 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.4640 inches and 0.5066 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Hexagon
End Application:
Agm129a
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Width Across Flats:
Between 0.1562 inches and 0.1580 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 100.0 degrees
Criticality Code Justification:
Anee and aaur
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response
Surface Treatment Specification:
Mil-c-83488, cl3, ty2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

## NSN 5305-01-380-7092

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.