## NSN 5305-01-380-7250



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-380-7250 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.112 inches **Fastener Length:** Between 0.491 inches and 0.511 inches **Head Style:** Flat fillister **Head Diameter:** 0.196 inches **Head Height:** 0.085 inches **Shoulder Diameter:** 0.1235 inches first shoulder and 0.1245 inches first shoulder **Shoulder Length:** 0.264 inches first shoulder and 0.284 inches first shoulder **Internal Drive Style:** Slot **End Application:** Pacer dawn **Thread Diameter:** 0.099 inches Thready Qty Per Inch (tpi): 56 **Criticality Code Justification:** Aatn and aatx **Shoulder Shape:** Round first shoulder **Special Features:** 0.015x45 degree chamfer thread end of shoulder and end of thread Material: Steel comp 303 **Surface Treatment Specification:** Mil-s-7720; cond-e military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-380-7250

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.