NSN 5305-01-380-8026

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-380-8026 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.300 inches **Fastener Length:** 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.700 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-380-8026

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.