

View Online at <https://aerobasegroup.com/nsn/5305-01-380-9330>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.363 inches

Fastener Length:

0.925 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.258 inches and 0.305 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Single Shear Strength:

132000 pounds per square inch

Internal Drive Style:

Offset cruciform (torque set)

End Application:

Pacer dawn

Thread Diameter:

0.190 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Anee and aaur

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.785 inches first hole

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 national specification 1st treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0