NSN 5305-01-381-0666

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-381-0666 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.460 inches **Fastener Length:** 1.500 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.427 inches and 0.439 inches **Extended Washer Diameter:** 0.400 inches **Extended Washer Thickness:** Between 0.020 inches and 0.030 inches **First Diameter From Head:** Between 0.198 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.925 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams 5643 cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

NSN 5305-01-381-0666

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0