NSN 5305-01-381-3769

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-381-3769 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.326 inches and 0.329 inches **Fastener Length:** Between 0.686 inches and 0.696 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** 0.277 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.315 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: 0.366 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 120.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 assn standard single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-381-3769

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0