NSN 5305-01-381-4305

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-381-4305 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.127 inches and 0.130 inches **Fastener Length:** 0.318 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.157 inches **First Diameter From Head:** Between 0.171 inches and 0.174 inches **Second Diameter From Head:** Between 0.183 inches and 0.186 inches **Third Diameter From Head:** Between 0.102 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.124 inches and 0.128 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.188 inches and 0.191 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: 0.085 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 **Product Name:** Navy special project Material: Steel comp 304l **Material Specification:** Astma276 assn standard single material response or qq-s-763 federal specification single material response

Passivate

Surface Treatment:

NSN 5305-01-381-4305

Externally Relieved Body Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0