

View Online at <https://aerobasegroup.com/nsn/5305-01-381-6320>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.444 inches

**Fastener Length:**

6.188 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.115 inches and 0.135 inches

**Width Between Flats:**

0.375 inches

**Shoulder Diameter:**

0.245 inches first shoulder and 0.255 inches first shoulder

**Shoulder Length:**

1.115 inches first shoulder and 1.120 inches first shoulder

**Internal Drive Style:**

W/o internal drive

**End Application:**

Pacer dawn

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Shoulder Shape:**

Round all shoulders

**Special Features:**

Grove 0.850 inches from head. 0.095 inches long and 0.190 dia; and a 60degree cone point, 0.164 inches long from the threaded end

**Material:**

Steel comp 630

**Material Specification:**

Ams5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072-e300 military specification all treatment responses

**Thread Series Designator:**

Unf

**Fsc Application Data:**

Idf blanker mounting

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072-e300 spec.