

View Online at <https://aerobasegroup.com/nsn/5305-01-381-6320>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.444 inches

Fastener Length:

6.188 inches

Head Style:

Hexagon

Head Height:

Between 0.115 inches and 0.135 inches

Width Between Flats:

0.375 inches

Shoulder Diameter:

0.245 inches first shoulder and 0.255 inches first shoulder

Shoulder Length:

1.115 inches first shoulder and 1.120 inches first shoulder

Internal Drive Style:

W/o internal drive

End Application:

Pacer dawn

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round all shoulders

Special Features:

Grove 0.850 inches from head. 0.095 inches long and 0.190 dia; and a 60degree cone point, 0.164 inches long from the threaded end

Material:

Steel comp 630

Material Specification:

Ams5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072-e300 military specification all treatment responses

Thread Series Designator:

Unf

Fsc Application Data:

Idf blanker mounting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-e300 spec.