NSN 5305-01-382-1306

Thread Class:

Right-hand **Thread Length:**0.363 inches

Thread Direction:

Fastener Length:

1.553 inches
Head Style:
Flat countersunk
Head Diameter:

2a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-382-1306

| Between 0.258 inches and 0.305 inches |
|--|
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Single Shear Strength: |
| 132000 pounds per square inch |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| End Application: |
| Pacer dawn |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.180 inches and 1.200 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Criticality Code Justification: |
| Anee and aaur |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams6487 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas672 national specification 1st treatment response |
| Thread Series Designator: |
| Unf |
| |
| |

NSN 5305-01-382-1306

Close Tolerance Screw - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | 0 | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0