NSN 5305-01-382-5957

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-382-5957 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.875 inches and 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 135000 pounds per square inch Hardness Rating: 28.0 rockwell c threads and 38.0 rockwell c threads Minimum Yield Strength: 105000 pounds per square inch Material: Steel comp 630 fastener **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Astm a380 assn standard single treatment response fastener **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-382-5957

Socket Head Cap Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.