NSN 5305-01-382-7474

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-382-7474 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.889 inches and 2.000 inches **Fastener Length:** Between 1.940 inches and 2.060 inches **Head Style:** Thumb no. 3 **Head Height:** Between 0.750 inches and 0.780 inches Width Between Flats: Between 0.670 inches and 0.700 inches **Shoulder Diameter:** 0.560 inches first shoulder and 0.590 inches first shoulder Point Style: Flat **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 48000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses and mil-c-81562, type 2, class 3 military specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-382-7474

Thumbscrew - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.