NSN 5305-01-383-3740

Thread Class:

A3a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-383-3740

Thread Direction:
Right-hand
Thread Length:
0.316 inches
Fastener Length:
1.378 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.497 inches and 0.507 inches
Hole Diameter:
0.076 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Hala Ossantitus
Hole Quantity:
1
1
1 Hole Type:
1 Hole Type: Drilled
1 Hole Type: Drilled Thready Qty Per Inch (tpi):
1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees Material:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees Material: Steel comp 4140
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees Material: Steel comp 4140 Material Specification:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees Material: Steel comp 4140 Material Specification: Mil-s-5626 military specification single material response
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch Hole Configuration Style: Round Countersink Angle: 99.0 degrees and 101.0 degrees Material: Steel comp 4140 Material Specification: Mil-s-5626 military specification single material response Surface Treatment:

NSN 5305-01-383-3740

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Specification Data:
80205-nas1154 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-5626 spec.