NSN 5305-01-383-3776

Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-383-3776

Thread Class: 2a Thread Direction: Right-hand Thread Length: Between 1.000 inches and 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate Thread Series Designator:
Right-hand Thread Length: Between 1.000 inches and 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Right-hand Thread Length: Between 1.000 inches and 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Thread Length: Between 1.000 inches and 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Between 1.000 inches and 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
2.250 inches Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Head Style: Hexagon Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Head Height: 0.243 inches Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Width Between Flats: 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
180000 pounds per square inch Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Hardness Rating: 40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
40.0 rockwell c threads and 48.0 rockwell c threads Minimum Yield Strength: 140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
140000 pounds per square inch Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Material: Steel comp 431 Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Material Specification: Astm f593 assn standard single material response Surface Treatment: Passivate
Astm f593 assn standard single material response Surface Treatment: Passivate
Surface Treatment: Passivate
Thread Series Designator:
<u> </u>
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0