

View Online at <https://aerobasegroup.com/nsn/5305-01-383-6029>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.407 inches and 0.438 inches

**Fastener Length:**

Between 0.479 inches and 0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.262 inches and 0.270 inches

**Head Height:**

Between 0.159 inches and 0.164 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Mrap - m-atv with cs13 pop and sne

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.1406 inches and 0.1426 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2170 pounds per square inch

**Special Features:**

Protective finish 1.9.2.3 Of mil-std-171, except .0003 thick.

**Color:**

Bronze or olive drab

**Material:**

Steel uns k03104

**Material Specification:**

Astm a574 assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633, type ii assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-std-171 spec.