

View Online at <https://aerobasegroup.com/nsn/5305-01-383-6029>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.407 inches and 0.438 inches

Fastener Length:

Between 0.479 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Internal Drive Style:

Hexagon

End Application:

Mrap - m-atv with cs13 pop and sne

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.1406 inches and 0.1426 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2170 pounds per square inch

Special Features:

Protective finish 1.9.2.3 Of mil-std-171, except .0003 thick.

Color:

Bronze or olive drab

Material:

Steel uns k03104

Material Specification:

Astm a574 assn standard single material response

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633, type ii assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.