NSN 5305-01-383-6046

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-383-6046 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.133 inches and 0.140 inches **Fastener Length:** 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.156 inches and 0.172 inches First Diameter From Head: Between 0.057 inches and 0.067 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.047 inches and 0.062 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 **Material Specification:** Astm a582 assn standard all material responses or mil-s-7720 military specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-383-6046

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.