## NSN 5305-01-383-6064

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-383-6064

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.425 inches

### Fastener Length:

0.863 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

Between 0.498 inches and 0.507 inches

#### **Grip Diameter:**

Between 0.2797 inches and 0.2807 inches

#### Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

## Grip Length:

Between 0.428 inches and 0.448 inches

### Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

6300 pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 4140

#### **Material Specification:**

Mil-s-5626 military specification single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416 ty2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

### Specification Data:

80205-nas1974 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5305-01-383-6064

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.