

View Online at <https://aerobasegroup.com/nsn/5305-01-383-6087>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.376 inches and 0.469 inches

**Fastener Length:**

Between 0.469 inches and 0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.3030 inches and 0.3125 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Mrap - m-atv with cs13 pop sne

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1406 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

2710 pounds per square inch

**Special Features:**

Protective finish 1.9.2.3 of mil-std-171, except .0003 thick.

**Color:**

Bronze or olive drab

**Material:**

Steel uns k03104

**Material Specification:**

Astm a574 assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633, type ii assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-std-171 spec.