NSN 5305-01-383-6087

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-383-6087 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.469 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.3030 inches and 0.3125 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **End Application:** Mrap - m-atv with cs13 pop sne **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1406 inches and 0.1587 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 2710 pounds per square inch **Special Features:** Protective finish 1.9.2.3 of mil-std-171, except .0003 thick. Color: Bronze or olive drab Material: Steel uns k03104 **Material Specification:** Astm a574 assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633, type ii assn standard single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-383-6087

Socket Head Cap Screw - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.