## NSN 5305-01-383-6097

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-383-6097

Thread Direction:         Sa         Thread Direction:         Right-hand         Thread Length:         0.375 inches         Fastener Length:         Between 0.798 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.306 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thread Quy Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 10.1 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unit Of Measure:         -         Pomilitarization:         Na         Distance From Head Largest Bearing Surface To Shank Hole Center:	Thread Class:
Thread Direction:         Right-hand         Thread Length:         0.375 inches         Fastener Length:         Between 0.798 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3016 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thread Quy Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.941 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unjf         Shelf Life:         Na         Unit Of Measure:         -         Permiliatrization:         Na         Steel         Thread Series Designato	
Right-hand         Thread Length:         0.375 inches         Fastener Length:         Between 0.798 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thread Valve Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Materiat:         Stell         Thread Stells Designator:         Unif         Na         Materiat:         Na         Dit Medsure:         Na         Ditance From Head Largest Bearing Company         Ditance From Head Largest Bearing Surface To Shank Hole Center:         <	
Tread Length:         0.375 inches         Fastener Length:         Between 0.798 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unjf         Shelf Life:         N/a         Unit of Measure:         ·         Permilitarization:         Na         Fig:	
0.375 inchesFastener Length:Between 0.798 inches and 0.828 inchesHead Style:Flat countersunkHead Diameter:Between 0.304 inches and 0.314 inchesGrip Diameter:Between 0.3106 inches and 0.3112 inchesShank Unthreaded Hole Diameter:0.076 inches and 0.086 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.312 inchesOrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):A24Countersink Angle:Between 99.0 degrees and 101.0 degreesDistance From Head Largest Bearing Surface To Shank Hole Center:0.994 inches bearing surface of headMaterial:SteelThread Steines Designator:UnjfShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	
Fastener Length:         Between 0.789 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shark Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         0.312 inches         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Pountersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Steries Designator:         Unjf         Shelf Life:         N/a         Ditt Of Measure:         Image:         No         Fig:	
Between 0.798 inches and 0.828 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Steise Designator:         Unif         Sheff Life:         N/a         Unit Of Measure:         To         Permilitarization:         No         Fig:	
Head Style:         Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unif         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	-
Flat countersunk         Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unif         Shell Infe:         N/a         Encilse Designator:         Va         Distance:         Dirief         Shell         Thread Series Designator:         Unif         Shell         Distance:         Distance:         Distance:         Distance:         Distance:         Distance:         Distance:	
Head Diameter:         Between 0.304 inches and 0.314 inches         Grip Diameter:         Between 0.3106 inches and 0.3112 inches         Shank Unthreaded Hole Diameter:         0.076 inches and 0.086 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unif         Sheft Life:         N/a         Unit of Measure:         C         Demilitarization:         No         Fig:	-
Between 0.304 inches and 0.314 inches Grip Diameter: Between 0.3106 inches and 0.3112 inches Shank Unthreaded Hole Diameter: 0.076 inches and 0.086 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Grip Diameter: Between 0.3106 inches and 0.3112 inches Shank Unthreaded Hole Diameter: 0.076 inches and 0.086 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 01.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: - Demilitarization: No	
Between 0.3106 inches and 0.3112 inches   Shank Unthreaded Hole Diameter:   0.076 inches and 0.086 inches   Internal Drive Style:   Cross recess type 1   Thread Diameter:   0.312 inches   Grip Length:   Between 0.428 inches and 0.448 inches   Thready Qty Per Inch (tpi):   A24   Countersink Angle:   Between 99.0 degrees and 101.0 degrees   Distance From Head Largest Bearing Surface To Shank Hole Center:   0.994 inches bearing surface of head   Material:   Steel   Thread Series Designator:   Unif   Shelf Life:   N/a   Unit of Measure:   -   Demilitarization:   No   Fig:	
Shank Unthreaded Hole Diameter:0.076 inches and 0.086 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):A24Countersink Angle:Between 99.0 degrees and 101.0 degreesDistance From Head Largest Bearing Surface To Shank Hole Center:0.994 inches bearing surface of headMaterial:SteelDiread Series Designator:UnifShelf Life:N/aDistor From Head Largest Hear (Largest Hear)NaFig:	-
0.076 inches and 0.086 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Internal Drive Style:Cross recess type 1Thread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):A24Countersink Angle:Between 99.0 degrees and 101.0 degreesDistance From Head Largest Bearing Surface To Shank Hole Center:0.994 inches bearing surface of headMaterial:SteelThread Series Designator:UnjfShelf Life:N/aDistor From Head Largest Bearing Surface To Shank Hole Center:DigSteelThread Series Designator:UnjfShelf Life:NaFiej:NoFiej:	
Cross recess type 1 Thread Diameter: 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Shelf Life: N/a Dist Of Measure:  Demilitarization: No	
Thread Diameter:         0.312 inches         Grip Length:         Between 0.428 inches and 0.448 inches         Thready Qty Per Inch (tpi):         A24         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Distance From Head Largest Bearing Surface To Shank Hole Center:         0.994 inches bearing surface of head         Material:         Steel         Thread Series Designator:         Unif         Shelf Life:         N/a         Ditt Of Measure:         Image:         No         Fig:	Internal Drive Style:
0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Diameter:
Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.312 inches
Thready Qty Per Inch (tpi):A24Countersink Angle:Between 99.0 degrees and 101.0 degreesDistance From Head Largest Bearing Surface To Shank Hole Center:0.994 inches bearing surface of headMaterial:SteelThread Series Designator:UnifShelf Life:N/aDint of Measure:Demilitarization:NoFig:	
A24 Countersink Angle: Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Between 0.428 inches and 0.448 inches
Countersink Angle:Between 99.0 degrees and 101.0 degreesDistance From Head Largest Bearing Surface To Shank Hole Center:0.994 inches bearing surface of headMaterial:SteelThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	A24
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Countersink Angle:
0.994 inches bearing surface of head Material: Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Between 99.0 degrees and 101.0 degrees
Material:SteelThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Distance From Head Largest Bearing Surface To Shank Hole Center:
Steel Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.994 inches bearing surface of head
Thread Series Designator:   Unjf   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Material:
Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Steel
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Unjf
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0