## NSN 5305-01-383-6116



Drive Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-383-6116 **Fastener Length:** Between 0.594 inches and 0.656 inches **Head Style:** Round **Head Diameter:** Between 0.236 inches and 0.242 inches **Head Height:** Between 0.155 inches and 0.170 inches **Pilot Diameter:** Between 0.198 inches and 0.202 inches Pilot Length: 0.078 inches **Features Provided:** Casehardened Nonmachine Thread Style: Drive screw (type u) **Nonmachine Thread Diameter:** 0.239 inches **Special Features:** Protective finish 1.9.2.3 of mil-std-171, except .0003 thick. Color: Bronze or olive drab Material: Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1021 or steel comp 1022 **Material Specification:** Aisi 1016 assn standard 1st material response or aisi 1018 assn standard 2nd material response or aisi 1019 assn standard 3rd material response or aisi 1021 assn standard 4th material response or aisi 1022 assn standard 5th material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633, type ii assn standard single treatment response Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

Mil-std (military Standard):

Mil-std-171 spec.

A003b0