## NSN 5305-01-383-6143

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-383-6143 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** 1.050 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.498 inches and 0.507 inches **Grip Diameter:** Between 0.2797 inches and 0.2807 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 6500 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 **Material Specification:** Mil-s-5626 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1974 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

## NSN 5305-01-383-6143

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.