

View Online at <https://aerobasegroup.com/nsn/5305-01-383-9062>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

0.925 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.498 inches and 0.507 inches

**Grip Diameter:**

Between 0.2797 inches and 0.2807 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

6300 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1974 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.