

View Online at <https://aerobasegroup.com/nsn/5305-01-384-0032>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.480 inches and 0.500 inches

**Fastener Length:**

Between 1.480 inches and 1.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.543 inches and 0.562 inches

**Head Height:**

Between 0.240 inches and 0.250 inches

**Shoulder Diameter:**

0.3710 inches first shoulder and 0.3730 inches first shoulder

**Shoulder Length:**

0.995 inches first shoulder and 1.005 inches first shoulder

**Single Shear Strength:**

3700 pounds per square inch

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

0.188 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

6170 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Make from ms51975-19. Strip cadmium plate in accordance with mil-s-5002 and surface treat with zinc.

**Material:**

Steel uns k03104

**Material Specification:**

Astm a574 assn standard single material response

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Qq-z-325, type ii, class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0